

# GEMSEAL MAVERICK

**PROTECTIVE TREATMENT OF INDUSTRIAL FLOORS IN CEMENT/CONCRETE AND QUARTZ.**



## TECHNICAL DATA SHEET

### PRODUCT DESCRIPTION

Resin-based formulation, in water solution, specific for the protective treatment of industrial floors in cement/concrete, quartz and very porous surfaces in general.

GEMSEAL MAVERICK creates a dense internal reticulation which seals the pores and prevents the absorption of staining substances and dirt in general, moreover, it prevents chalking and the leakage of cement dust. Specific product for any type of concrete product, installed both indoors and outdoors. The product is mainly applied in a single coat as it is, if necessary, with a maximum dilution of 30% with water, depending on the type of support to be treated, if the product is diluted, we recommend applying a further finishing coat after at least 4 hours.

### APPLICATION

Apply GEMSEAL MAVERICK with the normal accessories for the treatment of water-based products, therefore: brush, roller, microfiber cloths and similar accessories not impregnated with other products.

If 2 coats of the product are needed, apply the second in the opposite direction to guarantee total impregnating coverage. Walk on surfaces after 24 hours.

### ATTENTION

Handle the product with rubber gloves, in case the product comes into contact with skin or eyes it is recommended to rinse with plenty of water. Do not eat or drink during use. Avoid contact with eyes.

Keep the package tightly closed and out of the reach of children. It is advisable to always carry out test tests to check for any anomalies. Ready-to-use product, apply to dry substrates at temperatures above +10°C. It has limited resistance to acidic substances.

# GEMSEAL MAVERICK

**PROTECTIVE TREATMENT OF INDUSTRIAL  
FLOORS IN CEMENT/CONCRETE  
AND QUARTZ.**



## **IMPORTANT SAFETY NOTE**

When using any type of solvent based product suitable ventilation should be provided during and after application. Use appropriate rubber gloves where necessary and do not smoke, eat or drink while using product. Keep product well closed and out of the reach from children. Additional information available on the MSDS SHEET (Material Safety Data Sheet).

## **RECOMMENDED USE**

Suitable for all honed, flammmed texture granite, marble, natural and artificial engineered stones, terra cotta, quarry, cement pavers.

- Effective for interior and exterior use
- Effective for Flooring –Work surfaces (Kitchen, Bathrooms) Showers and areas in constant contact with water.

## **WARRANTY**

The technical advice whether verbal or in writing or by way of trials are given in good faith but without warranty. The application use or processing of the products are beyond our control and should be tested for their suitability and therefore your own responsibility. In no event shall GEMS ITALIA SRLS be liable to the customer or anyone else for incidental or consequential damages, however occasioned.

## **ALWAYS TEST FIRST**