

# GEMSEAL FLASH



## TECHNICAL DATA SHEET

### PRODUCT DESCRIPTION

GemSeal Flash protects and at the same time enhance the color of the stone. GemSeal Flash penetrates the surface of the stone creating an invisible barrier against moisture and rising humidity and protection against stains: Oil, Grease, Coffee, Tea, General Dirt, Food, Mould and Mildew. Product will not change the natural aspect of the stone or create any type of film, allowing permeability vapour moisture to escape, and is UV resistant. Some natural stones (marble, limestone) will remain sensitive to acidic etching, we recommend any spillage be cleaned up as a matter of good housekeeping.

### DRYING TIME

Fully effective within 48-72 hours before resuming normal use.

### COVERAGE PER LT

Indicative coverage allowing two coats subject to stone absorption, surface texture.

- High Porosity Stone, Sandstone 3 – 6m<sup>2</sup>
- Medium Porosity, Honed Stone,
- Low Porosity, Polished Stone 10 – 20m<sup>2</sup>
- Very Dense Stone: 25 – 30m<sup>2</sup>

**COVERAGE:** The information is purely a guide line only and may differ according to the porosity and textured finish of the stone and site conditions.



# GEMSEAL FLASH



## APPLICATION

All stone surfaces to be treated must be completely clean and dry. Where no previous treatment experience exists a small discreet area should be tested to verify the suitability of the product to the stone. Where necessary ensure all surrounding areas and surfaces sensitive to solvents are protected against any spillage. Apply one coat of GemSeal Flash evenly with a clean brush, a roller or by cloth in circular movements. On very absorbent surfaces apply a second coat allowing sufficient time for your first application to penetrate into the stone and dry. If in doubt test discreet area to ensure second application is necessary. In case of over treatment or any air bubbles remove by wiping excess product using a clean cotton cloth or absorbent paper. On large floor areas excess residue of product can be buffed off by machine using a white nylon type pad.

Temperature of surface to be treated should not be below 10°C. Avoid direct sunlight especially for external works.

## IMPORTANT SAFETY NOTE

When using any type of solvent based product suitable ventilation should be provided during and after application. Use appropriate rubber gloves where necessary and do not smoke, eat or drink while using product. Keep product well closed and out of the reach from children. Additional information available on the MSDS SHEET (Material Safety Data Sheet).

## STORAGE

Keep product in cool and dry surroundings.



# GEMSEAL FLASH



## RECOMMENDED USE

Suitable for all honed, flammmed texture granite, marble, natural and artificial engineered stones, terra cotta, quarry, cement pavers.

- Effective for interior and exterior use
- Effective for Flooring –Work surfaces (Kitchen, Bathrooms) Showers and areas in constant contact with water.

## WARRANTY

The technical advice whether verbal or in writing or by way of trials are given in good faith but without warranty. The application use or processing of the products are beyond our control and should be tested for their suitability and therefore your own responsibility. In no event shall GEMS ITALIA SRLS be liable to the customer or anyone else for incidental or consequential damages, however occasioned.

## ALWAYS TEST FIRST