

GEMSEAL HYDRO

NEUTRAL WATER REPELLENT
SOLVENT BASED



TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

HYDRO penetrates the surface of the stone creating an invisible barrier protection against stains caused by general dirt, mould and mildew. Product will not change the natural aspect of the stone or create any type of film, allowing permeability vapour moisture to escape, and is UV-resistant. Some natural stones (marble, limestone) will remain sensitive to acidic etching, we recommend any spillage be cleaned up as a matter of good housekeeping.

COVERAGE PER LT

Indicative coverage allowing two coats subject to stone absorption, surface texture.

- Honed or sandblasted stone between 3 – 6m²
- Surfaces with low porosity absorption 15 – 25m²

PACKAGING

- 10 x 1 litre
- 2 x 5 litre container
- 25 litre container

All childproof tamper evident cap

RECOMMENDED USE

Suitable for all honed, polished granite, marble, natural stones, terra cotta, masonry bricks, quarry, cement pavers and resin agglomerates.

- Effective treatment for exterior cladding and walls in constant contact with water and weathering.
- Effective water repellent action against general water, dirt, smog mould, mildew stains.

GEMSEAL HYDRO

NEUTRAL WATER REPELLENT
SOLVENT BASED



APPLICATION

All stone surfaces to be treated must be completely clean and dry. Where no previous treatment experience exists a small discreet area should be tested to verify the suitability of the product to the stone. Where necessary ensure all surrounding areas and surfaces sensitive to solvents are protected against any spillage. Apply one coat of HYDRO evenly by spraying using a low pressure pump up garden spray type unit or with a lamb's wool applicator or by cloth in circular movements. The most efficient method is by spraying. On very absorbent surfaces apply a second coat allowing sufficient time (Approx.3-4 hours) for your first application to penetrate into the stone and dry. If in doubt test discreet area to ensure second application is necessary. In case of over treatment or any air bubbles remove by wiping excess product using a clean cotton cloth or absorbent paper. Temperature of surface

to be treated should not be below 10°C. Avoid direct sunlight especially for external works.

DRYING TIME

Fully effective within 48-72 hours before resuming normal use.

IMPORTANT SAFETY NOTE

When using any type of treatment product suitable ventilation should be provided during and after application. Use appropriate rubber gloves where necessary and do not smoke, eat or drink while using product. Keep product well closed and out of the reach from children. Additional information available on the MSDS SHEET (Material Safety Data Sheet).

STORAGE

Keep product in cool and dry surroundings.

GEMSEAL HYDRO

NEUTRAL WATER REPELLENT
SOLVENT BASED



WARRANTY

The technical advice whether verbal or in writing or by way of trials are given in good faith but without warranty. The application use or processing of the products are beyond our control and should be tested for their suitability and therefore your own responsibility. In no event shall GEMS ITALIA SRLS be liable to the customer or anyone else for incidental or consequential damages, however occasioned.

ALWAYS TEST FIRST