

GEMSEAL PREMIUM

ADVANCED TECHNOLOGY - SOLVENT BASED



TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

PREMIUM penetrates the surface of the stone creating an invisible barrier against moisture and rising humidity and protection against stains: oil, grease, coffee, tea, food, general dirt, smog, mould and mildew. Product will not change the natural aspect of the stone or create any type of film, allowing permeability vapour moisture to escape, and is UV- resistant. Some natural stones (marble, limestone) will remain sensitive to acidic etching.

- Suitable for marble, granite, slate, sandstone, quartz, volcanic stones, concrete, cement, terra cotta, natural and artificial engineered stones.
- Effective for interior and exterior use.
- Odorless.
- Ideal for floors, kitchen tops, stairs, tables, bathroom tops and shelves.

PACKAGING

- 10 x 1 L bottle
- 2 x 5 L tank
- 1 x 25 L tank
- 10 x 200 ml bottle
- 10 x 500 ml bottle

All childproof tamper evident cap.

COVERAGE

Indicative coverage allowing 2 coats subject to stone asorption, surface texture.

- High Porosity Stone, Sandstone: 5 - 8 m²
- Medium Porosity, Honed Stone, Limestone 10 – 20m²
- Low Porosity, Polished Stone 20 – 25m²
- Very Dense Stone 25 – 30m²



GEMSEAL PREMIUM

ADVANCED TECHNOLOGY - SOLVENT BASED



APPLICATION

All stone surfaces to be treated must be completely clean and dry. Apply PREMIUM with roller, brush or by spraying. Remove any excess product. Apply one coat of PREMIUM evenly by spraying using a low pressure pump up garden spray type unit or with a lamb's wool applicator or by cloth in circular movements (for work tops). The most efficient method is by spraying. On very absorbent surfaces apply a second coat allowing sufficient time for your first application to penetrate into the stone and dry.

TEMPERATURE

Temperature of surface to be treated should not be below 10°C. Avoid direct sunlight especially for external works.

IMPORTANT SAFETY NOTE

When using any type of solvent based product suitable ventilation should be provided during and after application. Use appropriate rubber gloves where necessary and do not smoke, eat or drink while using product. Keep product well closed and out of the reach from children. Additional information available on the MSDS SHEET (Material Safety Data Sheet).

ADVICE

- On treated surfaces do not apply alcohol and solvent
- Keep product in cool and dry surroundings.
- Use appropriate rubber gloves where necessary and do not smoke, eat or drink while using product.



GEMSEAL PREMIUM

ADVANCED TECHNOLOGY - SOLVENT BASED



WARRANTY

The technical advice whether verbal or in writing or by way of trials are given in good faith but without warranty. The application use or processing of the products are beyond our control and should be tested for their suitability and therefore your own responsibility. In no event shall GEMS ITALIA SRLS be liable to the customer or anyone else for incidental or consequential damages, however occasioned.

ALWAYS TEST FIRST

