

# GEMSEAL ROOF

ANTI STAIN WATER BASED IMPREGNATOR  
TREATMENT MARBLE TERRAZZO



## TECHNICAL DATA SHEET

### PRODUCT DESCRIPTION

ROOF penetrates the surface of the stone creating an invisible barrier protection against stains: - Oil, Grease, Coffee, Tea, Food, General Dirt, Mould and Mildew. Product will not change the natural aspect of the stone or create any type of film, allowing permeability vapour moisture to escape, and is UV- resistant. Some natural stones (marble, limestone) will remain sensitive to acidic etching, we recommend any spillage be cleaned up as a matter of good housekeeping.

### APPLICATION

All stone surfaces to be treated must be completely clean and dry. Where no previous treatment experience exists a small discreet area should be tested to verify the suitability of the product to the stone.

Apply one coat of ROOF evenly by spraying using a low pressure pump up garden spray type unit or with a lamb's wool applicator or by cloth in circular movements. The most efficient method is by spraying. On very absorbent surfaces apply a second or third coat allowing sufficient time between each application (20-30 minutes) to penetrate into the stone and dry. If in doubt test discreet area to ensure second or third application is necessary.

In case of over treatment or any air bubbles remove by wiping excess product using a clean cotton cloth or absorbent paper. Temperature of surface to be treated should not be below 10°C. Avoid direct sunlight especially for external works.

# GEMSEAL ROOF

ANTI STAIN WATER BASED IMPREGNATOR  
TREATMENT MARBLE TERRAZZO



## RECOMMENDED USE

Polished and honed matt textured finish marble terrazzo, granite, marble, natural and artificial engineered stones, terra cotta, quarry, cement pavers.

- Natural finish for interior and exterior use
- Effective for honed and polished natural stones - Flooring –Work surfaces (Kitchen, Bathrooms)
- Effective as pre- grouting treatment

## DRYING TIME

Dry 2 to 3 hours, safe to walk on carefully. Fully effective within 48-72 hours before resuming normal use.

## PACKAGING

- 10 x 1 litre bottles
- 2 x 5 litre container
- 25 litre container

All childproof tamper evident cap

## IMPORTANT SAFETY NOTE

When using any type of product suitable ventilation should be provided during and after application. Use appropriate rubber gloves where necessary and do not smoke, eat or drink while using product. Keep product well closed and out of the reach from children. Additional information available on Material Safety Data Sheet.

# GEMSEAL ROOF

ANTI STAIN WATER BASED IMPREGNATOR  
TREATMENT MARBLE TERRAZZO



## COVERAGE PER LT

Indicative coverage allowing 2 coats  
subject to stone absorption, surface  
texture.

- High Porosity Stone, Sandstone 3 – 5m<sup>2</sup>
- Medium Porosity, Honed Stone,  
Limestone 6 – 10m<sup>2</sup>
- Low Porosity, Polished Stone 10 – 20m<sup>2</sup>
- Very Dense Stone 25 – 30m<sup>2</sup>

## PRE GROUT TREATMENT

Product can be applied while stone is  
damp. Apply over clean stone or tile  
surface minimum 3 hours before grouting.  
Final stone protection can be carried out  
with water based treatment later once  
stone clean and dry.

## WARRANTY

The technical advice whether verbal or  
in writing or by way of trials are given  
in good faith but without warranty. The  
application use or processing of the  
products are beyond our control and  
should be tested for their suitability  
and therefore your own responsibility.  
In no event shall GEMS ITALIA SRLS be  
liable to the customer or anyone else for  
incidental or consequential damages,  
however occasioned. **ALWAYS TEST  
FIRST**

## STORAGE

Keep product in cool and dry  
surroundings.